

Mr. Thomas Lund  
United States Mineral Products Company  
d/b/a Isolatek International  
P. O. Box 5006  
Huntington, IN 46750

Re: R 069-13323-00021  
First Reopening to Part 70 Operating  
Permit  
T 069-5660-00021

Dear Mr. Lund:

United States Mineral Products Company d/b/a Isolatek International was issued a Part 70 Operating Permit on December 28, 1999. The Office of Air Quality determined that it was necessary to reopen your Part 70 permit. Notice of the permit reopening pursuant to 326 IAC 2-7-9(c) was provided on August 16, 2000. The notice was published in the newspaper on February 22, 2002. No comments were received during the 30 day public notice comment period and the change is incorporated into your Part 70 permit.

As stated in the Notice, the language in 40 CFR Part 70.6(c)(5)(iii)(B)) was changed from "continuous or intermittent compliance" to "based on continuous or intermittent data" as part of the U.S. EPA's 1997 Compliance Assurance Monitoring rule making (Federal Register Volume 62, page 54900-54947, Wednesday, October 22, 1997). The U.S. District Court of Appeals, Washington D.C. ruled against EPA's language, saying that the Clean Air Act wording of continuous or intermittent compliance had to be used. (NRDC vs. EPA, #97-1727) Therefore, the following change is being made to your permit to be consistent with state and federal law.

Condition B.11(c)(3) is revised as follows:

---

B.11 Annual Compliance Certification [326 IAC 2-7-6(5)]

---

- (c) The annual compliance certification report shall include the following:
- (1) The appropriate identification of each term or condition of this permit that is the basis of the certification;
  - (2) The compliance status;
  - (3) Whether compliance was ~~based on~~ continuous or intermittent ~~data~~;
  - (4) The methods used for determining compliance of the source, currently and over the reporting period consistent with 326 IAC 2-7-5(3); and

- (5) Such other facts, as specified in Sections D of this permit, as IDEM, OAQ, may require to determine the compliance status of the source.

US Mineral Products Company  
d/b/a Isolatek International  
Huntington, Indiana  
Reviewer: Janet Mobley

Page 2 of 2  
Reopening No. 069-13323-00021  
Part 70 Permit No. T 069-5660-00021

The name of IDEM's "Office of Air Management" was changed to "Office of Air Quality" on January 1, 2001. All references to "Office of Air Management" in the permit pages have been changed to "Office of Air Quality" and all references to "OAM" have been changed to "OAQ".

All other conditions of the permit shall remain unchanged and in effect. Please find enclosed the revised Title V Operating Permit.

This decision is subject to the Indiana Administrative Orders and Procedures Act - IC 4-21.5-3-5. If you have any questions on this matter, please contact Janet Mobley, at (800) 451-6027, press 0 and ask for Janet Mobley or extension 2-8369, or dial (317) 232-8369.

Sincerely,

Paul Dubenetzky, Chief  
Permits Branch  
Office of Air Quality

PD/jm  
Attachments: Title V Permit  
cc: File - Huntington County  
Huntington County Health Department  
Air Compliance Section Inspector - Ryan Hillman  
Compliance Data Section - Karen Nowak  
Permit Review II - Janet Mobley

## **PART 70 OPERATING PERMIT OFFICE OF Air Quality**

**United States Mineral Products Company  
d.b.a. Isolatek International  
701 North Broadway  
Huntington, Indiana 46750**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 and 326 IAC 2-1-3.2 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: T 069-5660-00021	
Issued by: Janet G. McCabe, Assistant Commissioner Office of Air Quality	Issuance Date: December 28, 1999  Expiration Date: December 28, 2004

First Administrative Amendment No.: 069-11828-00021, issued on March 3, 2000  
Second Administrative Amendment No.: 069-12578-00021, issued on October 16, 2000

First Reopening No.: R 069-13323-00021	
Issued by: Paul Dubenetzky, Branch Chief Office of Air Quality	Issuance Date:

## TABLE OF CONTENTS

### A SOURCE SUMMARY

- A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]
- A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)]  
[326 IAC 2-7-5(15)]
- A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)]  
[326 IAC 2-7-5(15)]
- A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

### B GENERAL CONDITIONS

- B.1 Permit No Defense [326 IAC 2-1-10] [IC 13]
- B.2 Definitions [326 IAC 2-7-1]
- B.3 Permit Term [326 IAC 2-7-5(2)]
- B.4 Enforceability [326 IAC 2-7-7(a)]
- B.5 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]
- B.6 Severability [326 IAC 2-7-5(5)]
- B.7 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]
- B.8 Duty to Supplement and Provide Information [326 IAC 2-7-4(b)] [326 IAC 2-7-5(6)(E)]
- B.9 Compliance with Permit Conditions [326 IAC 2-7-5(6)(A)] [326 IAC 2-7-5(6)(B)]
- B.10 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]
- B.11 Annual Compliance Certification [326 IAC 2-7-6(5)]
- B.12 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1)  
and (6)] [326 IAC 1-6-3]
- B.13 Emergency Provisions [326 IAC 2-7-16]
- B.14 Permit Shield [326 IAC 2-7-15]
- B.15 Multiple Exceedances [326 IAC 2-7-5(1)(E)]
- B.16 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]
- B.17 Permit Modification, Reopening, Revocation and Reissuance, or Termination  
[326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]
- B.18 Permit Renewal [326 IAC 2-7-4]
- B.19 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]
- B.20 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)]
- B.21 Operational Flexibility [326 IAC 2-7-20]
- B.22 Construction Permit Requirement [326 IAC 2]
- B.23 Inspection and Entry [326 IAC 2-7-6(2)]
- B.24 Transfer of Ownership or Operation [326 IAC 2-1-6] [326 IAC 2-7-11]
- B.25 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)]
- B.26 Advanced Source Modification Approval [326 IAC 2-7-5(16)]

### C SOURCE OPERATION CONDITIONS

#### Emission Limitations and Standards [326 IAC 2-7-5(1)]

- C.1 Particulate Matter Emission Limitations For Processes with Process Weight Rates  
Less Than One Hundred (100) pounds per hour [326 IAC 6-3-2(c)]
- C.2 Opacity [326 IAC 5-1]
- C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]
- C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]
- C.5 Fugitive Dust Emissions [326 IAC 6-4]

- C.6 Operation of Equipment [326 IAC 2-7-6(6)]
- C.7 Stack Height [326 IAC 1-7]
- C.8 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61.140]

**Testing Requirements [326 IAC 2-7-6(1)]**

- C.9 Performance Testing [326 IAC 3-6]

**Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]**

- C.10 Compliance Schedule [326 IAC 2-7-6(3)]
- C.11 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]
- C.12 Maintenance of Monitoring Equipment [326 IAC 2-7-5(3)(A)(iii)]
- C.13 Monitoring Methods [326 IAC 3]
- C.14 Pressure Gauge Specifications

**Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]**

- C.15 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]
- C.16 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68.215]
- C.17 Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 2-7-5]  
[326 IAC 2-7-6] [326 IAC 1-6]
- C.18 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5]  
[326 IAC 2-7-6]

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

- C.19 Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-7-5(7)] [326 IAC 2-7-19(c)]  
[326 IAC 2-6]
- C.20 Monitoring Data Availability [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)]
- C.21 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]
- C.22 General Reporting Requirements [326 IAC 2-7-5(3)(C)]

**Stratospheric Ozone Protection**

- C.23 Compliance with 40 CFR 82 and 326 IAC 22-1

**D.1 FACILITY OPERATION CONDITIONS - Two (2) cupolas and two (2) blowchambers (EU#1 - #4)**

**Emission Limitations and Standards [326 IAC 2-7-5(1)]**

- D.1.1 Particulate Matter (PM) [326 IAC 6-3-2(c)]
- D.1.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

**Compliance Determination Requirements**

- D.1.3 Testing Requirements [326 IAC 2-7-6(1),(6)]
- D.1.4 Particulate Matter (PM)

**Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]**

- D.1.5 Visible Emissions Notations
- D.1.6 Parametric Monitoring
- D.1.7 Baghouse and Screenhouse Inspections
- D.1.8 Broken Bag or Failure Detection

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

- D.1.9 Record Keeping Requirements

**D.2 FACILITY OPERATION CONDITIONS - All Other Significant Emission Units**

**Emission Limitations and Standards [326 IAC 2-7-5(1)]**

- D.2.1 Particulate Matter (PM) [326 IAC 6-3]
- D.2.2 Prevention of Significant Deterioration [326 IAC 2-2]
- D.2.3 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

**Compliance Determination Requirements**

- D.2.4 Testing Requirements [326 IAC 2-7-6(1),(6)]
- D.2.5 Particulate Matter (PM)

**Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]**

- D.2.6 Visible Emissions Notations
- D.2.7 Parametric Monitoring
- D.2.8 Baghouse Inspections
- D.2.9 Broken Bag or Failure Detection

**Record Keeping and Reporting Requirement [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

- D.2.10 Record Keeping Requirements

**Certification Form**

**Emergency/Deviation Occurrence Report**

**Semi-Annual Compliance Monitoring Form**

## SECTION A

## SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

### A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]

---

The Permittee owns and operates a stationary acoustic and thermal insulation manufacturing source.

Responsible Official: Thomas Lund  
Source Address: 701 North Broadway, Huntington, Indiana 46750  
Mailing Address: P.O. Box 5006, Huntington, Indiana 46750  
SIC Code: 3296  
County Location: Huntington  
County Status: Attainment for all criteria pollutants  
Source Status: Part 70 Permit Program  
Major Source, under PSD Rules;  
Major Source, Section 112 of the Clean Air Act

### A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]

---

This stationary source consists of the following emission units and pollution control devices:

- (a) Two (2) short stack # 1 and # 2 cupolas, known as EU#1 and EU#2, installed before 1960, each equipped with a baghouse, known as CE#1 and CE#2, exhausted to Stack #1 and Stack #2, respectively, capacity: 7.2 tons of molten material per hour, each.
- (b) Two (2) blowchambers, known as EU#3 and EU#4, installed before 1978, each equipped with a screenhouse, known as CE#3 and CE#4, (#1 and #2 screenhouse), capacity: 6.0 tons of fibers per hour, each.
- (c) Three (3) hoppers, known as EU#14, EU#15 and EU#17 (hopper #1, #2 and #4), installed in 1980, equipped with a baghouse, known as CE#9, exhausted to Stack #9, capacity: 5.0 tons of dry powdered binders per hour, each.
- (d) Two (2) hoppers, known as EU#16 and EU#18 (hopper #3 and #5), installed in 1980, equipped with a baghouse, known as CE#9, exhausted to Stack #9, capacity: 0.2 ton of dry powdered binders per hour, each.
- (e) One (1) live bottom hopper, known as EU#19, installed in 1980, equipped with a baghouse, known as CE#9, exhausted to Stack #9, capacity: 8.0 tons of mineral wool per hour.
- (f) One (1) granulator, known as EU#20, installed in 1980, equipped with a baghouse, known as CE#9, exhausted to Stack #9, capacity: 8.0 tons of mineral wool per hour.
- (g) One (1) bagger, known as EU#21, installed in 1980, equipped with a baghouse, known as CE#9, exhausted to Stack #9, capacity: 12.0 tons of blended product per hour.

- (h) Two (2) augers, known as EU#23 and EU#24, installed in 1980, equipped with a baghouse, known as CE#9, exhausted to Stack #9, capacity: 12.0 tons of blended product per hour, each.
- (i) One (1) portable hopper, known as EU#27 (portable hopper #3), installed in 1980, equipped with a baghouse, known as CE#9, exhausted to Stack #9, capacity: 0.2 ton of dry powdered binders per hour.
- (j) One (1) hammermill/cyclone, known as EU#28, installed in 1980, equipped with a baghouse, known as CE#9, exhausted to Stack #9, capacity: 2.0 tons of mineral wool per hour.
- (k) Two (2) portable hoppers, known as EU#25 and EU#26, (portable hoppers #1 and #2, respectively), installed in 1980, exhausted inside the building, capacity: 0.75 tons of dry powdered binders per hour, each.
- (l) Two (2) mineral wool balers, known as EU#5 and EU#6, installed before 1980, exhausted inside the building, capacity: 6.0 tons of baled mineral wool per hour, each.
- (m) One (1) front end mineral wool bagger, known as EU#7, installed in 1987, equipped with a baghouse, known as CE#5, exhausted to Stack #5, capacity: 5.0 tons of bagged mineral wool per hour.
- (n) One (1) mineral wool bin, known as EU#8, installed in 1983 or 1984, equipped with a pneumatic conveyor that incorporates a totally enclosed air recycled system, capacity: 10.0 tons of mineral wool per hour.
- (o) One (1) gypsum silo, known as EU#9, installed before 1980, equipped with a baghouse, known as CE#8, exhausted to Stack #8, capacity: 54.0 tons of gypsum per hour.
- (p) One (1) chipped gypsum silo, known as EU#10, installed in 1991, equipped with a baghouse, known as CE#8, exhausted to Stack #8, capacity: 54.0 tons of gypsum per hour.
- (q) One (1) cement silo, known as EU#11, installed in 1990, equipped with a baghouse, known as CE#7, exhausted to Stack #7, capacity: 54.0 tons of Portland cement per hour.
- (r) One (1) batch blender, known as EU#12, installed in 1993, equipped with a baghouse, known as CE#6, exhausted to Stack #6, capacity: 5.0 tons of blended product per hour.
- (s) One (1) debaler, known as EU#13, installed in 1980, exhausted inside the building, capacity: 5.0 tons of mineral wool per hour.
- (t) One (1) raw material receiving yard, known as EU#29, installed prior to 1980, capacity: 216 tons of rock, slag and coke per hour.
- (u) One (1) batching station, known as EU#30, installed prior to 1980, capacity: 14.4 tons of rock and coke per hour.
- (v) One (1) ribbon blender, known as EU# 31, installed in 1988, equipped with a baghouse, known as CE#6, exhausted to Stack #6, capacity: 2.0 tons of dry powdered binders per year.
- (w) One (1) dedust oil tank, known as EU#34, installed prior to 1980, exhausted to Stack # 17,



capacity: 7,000 gallons.

- (x) One (1) PEG400 VOC tank, known as EU#35, installed in 1990, capacity: 8,000 gallons.
- (y) One (1) Dedust oil tank, known as EU#38, installed in 1997, exhausted to Stack #21, capacity: 8,000 gallons.
- (z) Removed by AAT 069-12578.
- (aa) One (1) mixed binder surge hopper scale system, known as EU#40, installed in 2000, equipped with an existing baghouse, known as CE#9, exhausted to Stack #9, capacity: 5.0 tons of powdered binders per hour.

A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)]  
[326 IAC 2-7-5(15)]

---

This stationary source does not currently have any insignificant activities, as defined in 326 IAC 2-7-1 (21) that have applicable requirements.

A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

---

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because:

- (a) It is a major source, as defined in 326 IAC 2-7-1(22);
- (b) It is a source in a source category designated by the United States Environmental Protection Agency (U.S. EPA) under 40 CFR 70.3 (Part 70 - Applicability).

**SECTION B GENERAL CONDITIONS**

**B.1 Permit No Defense [326 IAC 2-1-10] [IC 13]**

- (a) Indiana statutes from IC 13 and rules from 326 IAC, quoted in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a Part 70 permit under 326 IAC 2-7.
- (b) This prohibition shall not apply to alleged violations of applicable requirements for which the Commissioner has granted a permit shield in accordance with 326 IAC 2-1-3.2 or 326 IAC 2-7-15, as set out in this permit in the Section B condition entitled "Permit Shield."

**B.2 Definitions [326 IAC 2-7-1]**

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, any applicable definitions found in IC 13-11, 326 IAC 1-2 and 326 IAC 2-7 shall prevail.

**B.3 Permit Term [326 IAC 2-7-5(2)]**

This permit is issued for a fixed term of five (5) years from the effective date, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3.

**B.4 Enforceability [326 IAC 2-7-7(a)]**

- (a) All terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM.
- (b) Unless otherwise stated, terms and conditions of this permit, including any provisions to limit the source's potential to emit, are enforceable by the United States Environmental Protection Agency (U.S. EPA) and citizens under the Clean Air Act.

**B.5 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]**

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-7-3 and 326 IAC 2-7-4(a).

**B.6 Severability [326 IAC 2-7-5(5)]**

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

**B.7 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]**

This permit does not convey any property rights of any sort, or any exclusive privilege.

**B.8 Duty to Supplement and Provide Information [326 IAC 2-7-4(b)] [326 IAC 2-7-5(6)(E)]**

- (a) The Permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue, P. O. Box 6015  
Indianapolis, Indiana 46206-6015

- (b) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that

IDEM, OAQ, may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit.

- (c) Upon request, the Permittee shall also furnish to IDEM, OAQ, copies of records required to be kept by this permit. If the Permittee wishes to assert a claim of confidentiality over any of the furnished records, the Permittee must furnish such records to IDEM, OAQ, along with a claim of confidentiality under 326 IAC 17. If requested by IDEM, OAQ, or the U.S. EPA, to furnish copies of requested records directly to U. S. EPA, and if the Permittee is making a claim of confidentiality regarding the furnished records, then the Permittee must furnish such confidential records directly to the U.S. EPA along with a claim of confidentiality under 40 CFR 2, Subpart B.

**B.9 Compliance with Permit Conditions [326 IAC 2-7-5(6)(A)] [326 IAC 2-7-5(6)(B)]**

---

- (a) The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit, except those specifically designated as not federally enforceable, constitutes a violation of the Clean Air Act and is grounds for:
  - (1) Enforcement action;
  - (2) Permit termination, revocation and reissuance, or modification; or
  - (3) Denial of a permit renewal application.
- (b) It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

**B.10 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]**

---

- (a) Where specifically designated by this permit or required by an applicable requirement, any application forms, report, or compliance certification submitted under this permit shall contain certification by a responsible official of truth, accuracy, and completeness. This certification, shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, on the attached Certification Form, with each submittal.
- (c) A responsible official is defined at 326 IAC 2-7-1(34).

**B.11 Annual Compliance Certification [326 IAC 2-7-6(5)]**

---

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. The certification shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in letter form no later than July 1 of each year to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue, P. O. Box 6015  
Indianapolis, Indiana 46206-6015

and

United States Mineral Products Company First Reopening No.: 069-13323  
d.b.a. Isolatek International Reopening by: Janet Mobley  
Huntington, Indiana  
Permit Reviewer:MES

Page 10 of 51  
OP No. T 069-5660-00021

United States Environmental Protection Agency, Region V  
Air and Radiation Division, Air Enforcement Branch - Indiana (AE-17J)  
77 West Jackson Boulevard  
Chicago, Illinois 60604-3590

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
  - (1) The identification of each term or condition of this permit that is the basis of the certification;
  - (2) The compliance status;
  - (3) Whether compliance was continuous or intermittent;
  - (4) The methods used for determining compliance of the source, currently and over the reporting period consistent with 326 IAC 2-7-5(3); and
  - (5) Such other facts, as specified in Sections D of this permit, as IDEM, OAQ, may require to determine the compliance status of the source.

The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

B.12 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)]  
[326 IAC 1-6-3]

- 
- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMP) within ninety (90) days after issuance of this permit, including the following information on each facility:
    - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
    - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions;
    - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If due to circumstances beyond its control, the PMP cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue, P. O. Box 6015

Indianapolis, Indiana 46206-6015

- (b) The Permittee shall implement the Preventive Maintenance Plans as necessary to ensure that failure to implement the Preventive Maintenance Plan does not cause or contribute to a violation of any limitation on emissions or potential to emit.
- (c) PMP's shall be submitted to IDEM, OAQ, upon request and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ, may require the Permittee to revise its Preventive Maintenance Plan whenever lack of proper maintenance causes or contributes to any violation.

**B.13 Emergency Provisions [326 IAC 2-7-16]**

---

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation, except as provided in 326 IAC 2-7-16.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a health-based or technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:
  - (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
  - (2) The permitted facility was at the time being properly operated;
  - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
  - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone Number: 1-800-451-6027 (ask for Office of Air Quality, Compliance Section), or

Telephone Number: 317-233-5674 (ask for Compliance Section)

Facsimile Number: 317-233-5967

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted notice, either in writing or facsimile, of the emergency to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue, P. O. Box 6015  
Indianapolis, Indiana 46206-6015

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
- (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions) for sources subject to this rule after the effective date of this rule. This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
- (e) IDEM, OAQ, may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4(c)(9) be revised in response to an emergency.
- (f) Failure to notify IDEM, OAQ, by telephone or facsimile of an emergency lasting more than one (1) hour in compliance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.
- (g) Operations may continue during an emergency only if the following conditions are met:
  - (1) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
  - (2) If an emergency situation causes a deviation from a health-based limit, the Permittee may not continue to operate the affected emissions facilities unless:
    - (A) The Permittee immediately takes all reasonable steps to correct the emergency situation and to minimize emissions; and
    - (B) Continued operation of the facilities is necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value.

Any operation shall continue no longer than the minimum time required to prevent the situations identified in (g)(2)(B) of this condition.

**B.14 Permit Shield [326 IAC 2-7-15]**

---

- (a) This condition provides a permit shield as addressed in 326 IAC 2-7-15.
- (b) This permit shall be used as the primary document for determining compliance with applicable requirements established by previously issued permits. Compliance with the conditions of this permit shall be deemed in compliance with any applicable requirements as of the date of permit issuance, provided that:

- (1) The applicable requirements are included and specifically identified in this permit; or



- (2) The permit contains an explicit determination or concise summary of a determination that other specifically identified requirements are not applicable.
- (c) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, including any term or condition from a previously issued construction or operation permit, IDEM, OAQ, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.
- (d) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application. Erroneous information means information that the Permittee knew to be false, or in the exercise of reasonable care should have been known to be false, at the time the information was submitted.
- (e) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:
  - (1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;
  - (2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;
  - (3) The applicable requirements of the acid rain program, consistent with Section 408 (a) of the Clean Air Act; and
  - (4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.
- (f) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).
- (g) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAQ, has issued the modifications. [326 IAC 2-7-12(c)(7)]
- (h) This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAQ, has issued the modification. [326 IAC 2-7-12(b)(8)]

**B.15 Multiple Exceedances [326 IAC 2-7-5(1)(E)]**

Any exceedance of a permit limitation or condition contained in this permit, which occurs contemporaneously with an exceedance of an associated surrogate or operating parameter established to detect or assure compliance with that limit or condition, both arising out of the same act or occurrence, shall constitute a single potential violation of this permit.

**B.16 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]**

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provisions), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

United States Mineral Products Company First Reopening No.: 069-13323  
d.b.a. Isolatek International Reopening by: Janet Mobley  
Huntington, Indiana  
Permit Reviewer:MES

Page 16 of 51  
OP No. T 069-5660-00021

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

within ten (10) calendar days from the date of the discovery of the deviation.

- (b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit or a rule. It does not include:
- (1) An excursion from compliance monitoring parameters as identified in Section D of this permit unless tied to an applicable rule or limit; or
  - (2) An emergency as defined in 326 IAC 2-7-1(12); or
  - (3) Failure to implement elements of the Preventive Maintenance Plan unless such failure has caused or contributed to a deviation.
  - (4) Failure to make or record information required by the compliance monitoring provisions of Section D unless such failure exceeds 5% of the required data in any calendar quarter.

A Permittee's failure to take the appropriate response step when an excursion of a compliance monitoring parameter has occurred is a deviation.

- (c) Written notification shall be submitted on the attached Emergency/Deviation Occurrence Reporting Form or its substantial equivalent. The notification does not need to be certified by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (d) Proper notice submittal under 326 IAC 2-7-16 satisfies the requirement of this subsection.

**B.17 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-7-5(6)(C)]**  
**[326 IAC 2-7-8(a)] [326 IAC 2-7-9]**

---

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Part 70 permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-7-5(6)(C)]
- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ, determines any of the following:
- (1) That this permit contains a material mistake.
  - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
  - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-7-9(a)(3)]
- (c) Proceedings by IDEM, OAQ, to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which

cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-7-9(b)]

- (d) The reopening and revision of this permit, under 326 IAC 2-7-9(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ, at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ, may provide a shorter time period in the case of an emergency. [326 IAC 2-7-9(c)]

**B.18 Permit Renewal [326 IAC 2-7-4]**

---

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ, and shall include the information specified in 326 IAC 2-7-4. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

- (b) Timely Submittal of Permit Renewal [326 IAC 2-7-4(a)(1)(D)]

- (1) A timely renewal application is one that is:

- (A) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
- (B) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

- (2) If IDEM, OAQ, upon receiving a timely and complete permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.

- (c) Right to Operate After Application for Renewal [326 IAC 2-7-3]

If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-7 until IDEM, OAQ, takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ, any additional information identified as being needed to process the application.

- (d) United States Environmental Protection Agency Authority [326 IAC 2-7-8(e)]

If IDEM, OAQ, fails to act in a timely way on a Part 70 permit renewal, the U.S. EPA may invoke its authority under Section 505(e) of the Clean Air Act to terminate or revoke and

reissue a Part 70 permit.

**B.19 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]**

---

(a) The Permittee must comply with the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this permit.

(b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

Any such application should be certified by the "responsible official" as defined by 326 IAC 2-7-1(34) only if a certification is required by the terms of the applicable rule.

(c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

**B.20 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)]  
[326 IAC 2-7-12 (b)(2)]**

---

(a) No Part 70 permit revision shall be required under any approved economic incentives, marketable Part 70 permits, emissions trading, and other similar programs or processes for changes that are provided for in a Part 70 permit.

(b) Notwithstanding 326 IAC 2-7-12(b)(1)(D)(i) and 326 IAC 2-7-12(c)(1), minor Part 70 permit modification procedures may be used for Part 70 modifications involving the use of economic incentives, marketable Part 70 permits, emissions trading, and other similar approaches to the extent that such minor Part 70 permit modification procedures are explicitly provided for in the applicable State Implementation Plan (SIP) or in applicable requirements promulgated or approved by the U.S. EPA.

**B.21 Operational Flexibility [326 IAC 2-7-20]**

---

(a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-7-20(b), (c), or (e), without a prior permit revision, if each of the following conditions is met:

- (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
- (2) Any approval required by 326 IAC 2-1.1 has been obtained;
- (3) The changes do not result in emissions which exceed the emissions allowable under this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
- (4) The Permittee notifies the:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue, P. O. Box 6015  
Indianapolis, Indiana 46206-6015

United States Mineral Products Company First Reopening No.: 069-13323  
d.b.a. Isolatek International Reopening by: Janet Mobley  
Huntington, Indiana  
Permit Reviewer:MES

Page 20 of 51  
OP No. T 069-5660-00021

and

United States Environmental Protection Agency, Region V  
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)  
77 West Jackson Boulevard  
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site which document, on a rolling five (5) year basis, all such changes and emissions trading that are subject to 326 IAC 2-7-20 (b), (c), or (e) and makes such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ, in the notices specified in 326 IAC 2-7-20(b), (c)(1), and (e)(2).

- (b) The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-7-20(a) and the following additional conditions:

- (1) The permit shield, described in 326 IAC 2-7-15, shall not apply to any change made under 326 IAC 2-7-20(b).
- (2) For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:
  - (i) A brief description of the change within the source;
  - (ii) The date on which the change will occur;
  - (iii) Any change in emissions; and
  - (iv) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) Emission Trades [326 IAC 2-7-20(c)]  
The Permittee may trade increases and decreases in emissions in the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-7-20(c).
- (d) Alternative Operating Scenarios [326 IAC 2-7-20(d)]  
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-7-5(9). No prior notification of IDEM, OAQ, or U.S. EPA is required.
- (e) Backup fuel switches specifically addressed in, and limited under, Section D of this permit shall not be considered alternative operating scenarios. Therefore, the notification require-

ments of part (a) of this condition do not apply.

**B.22 Construction Permit Requirement [326 IAC 2]**

A modification, construction, or reconstruction shall be approved if required by and in accordance with the applicable provisions of 326 IAC 2.

**B.23 Inspection and Entry [326 IAC 2-7-6(2)]**

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a Part 70 source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) Inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) Sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) Utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.  
[326 IAC 2-7-6(6)]

**B.24 Transfer of Ownership or Operational Control [326 IAC 2-7-11]**

- (a) The Permittee must comply with the requirements of 326 IAC 2-7-11 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

The application which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

**B.25 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)]**



- 
- (a) The Permittee shall pay annual fees to IDEM, OAQ, within thirty (30) calendar days of receipt of a billing. If the Permittee does not receive a bill from IDEM, OAQ, the applicable fee is due April 1 of each year.
  - (b) Except as provided in 326 IAC 2-7-19(e), failure to pay may result in administrative enforcement action or revocation of this permit.
  - (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-0425 (ask for OAQ, Technical Support and Modeling Section), to determine the appropriate permit fee.

**B.26 Advanced Source Modification Approval [326 IAC 2-7-5(16)]**

---

The requirements to obtain a source modification approval under 326 IAC 2-7-10.5 or a permit modification under 326 IAC 2-7-12 are satisfied by this permit for the proposed emission units, control equipment or insignificant activities in Sections A.2 and A.3 if such modifications occur during the term of this permit.

## SECTION C

## SOURCE OPERATION CONDITIONS

Entire Source
---------------

### Emission Limitations and Standards [326 IAC 2-7-5(1)]

**C.1 Particulate Matter Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) pounds per hour [326 IAC 6-3-2(c)]**

Pursuant to 326 IAC 6-3-2(c), the allowable particulate matter emissions rate from any process not already regulated by 326 IAC 6-1 or any New Source Performance Standard, and which has a maximum process weight rate less than 100 pounds per hour shall not exceed 0.551 pounds per hour.

**C.2 Opacity [326 IAC 5-1]**

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemption Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

**C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]**

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1. 326 IAC 4-1-3 (a)(2)(A) and (B) are not federally enforceable.

**C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]**

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2. The provisions of 326 IAC 9-1-2 are not federally enforceable.

**C.5 Fugitive Dust Emissions [326 IAC 6-4]**

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.

**C.6 Operation of Equipment [326 IAC 2-7-6(6)]**

Except as otherwise provided in this permit, all air pollution control equipment listed in this permit and used to comply with an applicable requirement shall be operated at all times that the emission units vented to the control equipment are in operation.

**C.7 Stack Height [326 IAC 1-7]**

The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted.

United States Mineral Products Company First Reopening No.: 069-13323  
d.b.a. Isolatek International Reopening by: Janet Mobley  
Huntington, Indiana  
Permit Reviewer:MES

Page 25 of 51  
OP No. T 069-5660-00021

C.8 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61.140]

---

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
  - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
  - (2) If there is a change in the following:
    - (A) Asbestos removal or demolition start date;
    - (B) Removal or demolition contractor; or
    - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management  
Asbestos Section, Office of Air Quality  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

The notifications do not require a certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (e) Procedures for Asbestos Emission Control  
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-4 emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) Indiana Accredited Asbestos Inspector  
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement that the inspector be accredited is federally enforceable.

### Testing Requirements [326 IAC 2-7-6(1)]

#### C.9 Performance Testing [326 IAC 3-6]

---

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue, P. O. Box 6015  
Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days prior to the intended test date. The Permittee shall submit a notice of the actual test date to the above address so that it is received at least two weeks prior to the test date.

- (b) All test reports must be received by IDEM, OAQ within forty-five (45) days after the completion of the testing. An extension may be granted by the IDEM, OAQ, if the source submits to IDEM, OAQ, a reasonable written explanation within five (5) days prior to the end of the initial forty-five (45) day period.

The documentation submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

### Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

#### C.10 Compliance Schedule [326 IAC 2-7-6(3)]

---

The Permittee:

- (a) Has certified that all facilities at this source are in compliance with all applicable requirements; and
- (b) Has submitted a statement that the Permittee will continue to comply with such requirements; and
- (c) Will comply with such applicable requirements that become effective during the term of this permit.

#### C.11 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

---

Compliance with applicable requirements shall be documented as required by this permit. All monitoring and record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. If due to circumstances beyond its control, that equipment cannot be installed and operated within ninety (90) days, the Permittee may extend the compliance schedule related to the equipment for an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue, P. O. Box 6015  
Indianapolis, Indiana 46206-6015

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

**C.12 Maintenance of Monitoring Equipment [326 IAC 2-7-5(3)(A)(iii)]**

---

- (a) In the event that a breakdown of the monitoring equipment occurs, a record shall be made of the times and reasons of the breakdown and efforts made to correct the problem. To the extent practicable, supplemental or intermittent monitoring of the parameter should be implemented at intervals no less frequent than required in Section D of this permit until such time as the monitoring equipment is back in operation. In the case of continuous monitoring, supplemental or intermittent monitoring of the parameter should be implemented at intervals no less than one (1) hour until such time as the continuous monitor is back in operation.
- (b) The Permittee shall install, calibrate, quality assure, maintain, and operate all necessary monitors and related equipment. In addition, prompt corrective action shall be initiated whenever indicated.

**C.13 Monitoring Methods [326 IAC 3]**

---

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, or other approved methods as specified in this permit.

**C.14 Pressure Gauge Specifications**

---

Whenever a condition in this permit requires the measurement of pressure drop across any part of the unit or its control device, the gauge employed shall have a scale such that the expected normal reading shall be no less than twenty percent (20%) of full scale and be accurate within plus or minus two percent ( $\pm 2\%$ ) of full scale reading.

**Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]**

**C.15 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]**

---

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

- (a) The Permittee shall prepare written emergency reduction plans (ERPs) consistent with safe operating procedures.
- (b) These ERPs shall be submitted for approval to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

within ninety (90) days after the date of issuance of this permit.

United States Mineral Products Company First Reopening No.: 069-13323  
d.b.a. Isolatek International Reopening by: Janet Mobley  
Huntington, Indiana  
Permit Reviewer:MES

Page 29 of 51  
OP No. T 069-5660-00021

The ERP does not require the certification by the “responsible official” as defined by 326 IAC 2-7-1(34).

- (c) If the ERP is disapproved by IDEM, OAQ, the Permittee shall have an additional thirty (30) days to resolve the differences and submit an approvable ERP.
- (d) These ERPs shall state those actions that will be taken, when each episode level is declared, to reduce or eliminate emissions of the appropriate air pollutants.
- (e) Said ERPs shall also identify the sources of air pollutants, the approximate amount of reduction of the pollutants, and a brief description of the manner in which the reduction will be achieved.
- (f) Upon direct notification by IDEM, OAQ, that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level. [326 IAC 1-5-3]

C.16 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68.215]

If a regulated substance, subject to 40 CFR 68, is present in a process in more than the threshold quantity, 40 CFR 68 is an applicable requirement and the Permittee shall:

- (a) Submit:
  - (1) A compliance schedule for meeting the requirements of 40 CFR 68 by the date provided in 40 CFR 68.10(a); or
  - (2) As a part of the compliance certification submitted under 326 IAC 2-7-6(5), a certification statement that the source is in compliance with all the requirements of 40 CFR 68, including the registration and submission of a Risk Management Plan (RMP); and
  - (3) A verification to IDEM, OAQ, that a RMP or a revised plan was prepared and submitted as required by 40 CFR 68.
- (b) Provide annual certification to IDEM, OAQ, that the Risk Management Plan is being properly implemented.

All documents submitted pursuant to this condition shall include the certification by the “responsible official” as defined by 326 IAC 2-7-1(34).

C.17 Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 2-7-5][326 IAC 2-7-6] [326 IAC 1-6]

- (a) The Permittee is required to implement a compliance monitoring plan to ensure that reasonable information is available to evaluate its continuous compliance with applicable requirements. This compliance monitoring plan is comprised of:
  - (1) This condition;
  - (2) The Compliance Determination Requirements in Section D of this permit;
  - (3) The Compliance Monitoring Requirements in Section D of this permit;



United States Mineral Products Company First Reopening No.: 069-13323  
d.b.a. Isolatek International Reopening by: Janet Mobley  
Huntington, Indiana  
Permit Reviewer:MES

Page 31 of 51  
OP No. T 069-5660-00021

- (4) The Record Keeping and Reporting Requirements in Section C (Monitoring Data Availability, General Record Keeping Requirements, and General Reporting Requirements) and in Section D of this permit; and
- (5) A Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. CRP's shall be submitted to IDEM, OAQ upon request and shall be subject to review and approval by IDEM, OAQ. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee and maintained on site, and is comprised of:
  - (A) Response steps that will be implemented in the event that compliance related information indicates that a response step is needed pursuant to the requirements of Section D of this permit; and
  - (B) A time schedule for taking such response steps including a schedule for devising additional response steps for situations that may not have been predicted.
- (b) For each compliance monitoring condition of this permit, appropriate response steps shall be taken when indicated by the provisions of that compliance monitoring condition. Failure to perform the actions detailed in the compliance monitoring conditions or failure to take the response steps within the time prescribed in the Compliance Response Plan, shall constitute a violation of the permit unless taking the response steps set forth in the Compliance Response Plan would be unreasonable.
- (c) After investigating the reason for the excursion, the Permittee is excused from taking further response steps for any of the following reasons:
  - (1) The monitoring equipment malfunctioned, giving a false reading. This shall be an excuse from taking further response steps providing that prompt action was taken to correct the monitoring equipment.
  - (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for an administrative amendment to the permit, and such request has not been denied or;
  - (3) An automatic measurement was taken when the process was not operating; or
  - (4) The process has already returned to operating within "normal" parameters and no response steps are required.
- (d) Records shall be kept of all instances in which the compliance related information was not met and of all response steps taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.

**C.18 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5] [326 IAC 2-7-6]**

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate corrective actions. The Permittee shall submit a description of these corrective actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The

Permittee shall take appropriate action to minimize emissions from the affected facility while the corrective actions are being implemented. IDEM, OAQ shall notify the Permittee within thirty (30) days, if the corrective actions taken are deficient. The Permittee shall submit a description of additional corrective actions taken to IDEM, OAQ within thirty (30) days of receipt of the notice of deficiency. IDEM, OAQ reserves the authority to use enforcement activities to resolve noncompliant stack tests.

- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline. Failure of the second test to demonstrate compliance with the appropriate permit conditions may be grounds for immediate revocation of the permit to operate the affected facility.

The documents submitted pursuant to this condition do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

#### **Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

##### **C.19 Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-7-5(7)] [326 IAC 2-7-19(c)] [326 IAC 2-6]**

- (a) The Permittee shall submit an annual emission statement certified pursuant to the requirements of 326 IAC 2-6, that must be received by July 1 of each year and must comply with the minimum requirements specified in 326 IAC 2-6-4. The annual emission statement shall meet the following requirements:
- (1) Indicate actual emissions of criteria pollutants from the source, in compliance with 326 IAC 2-6 (Emission Reporting);
  - (2) Indicate actual emissions of other regulated pollutants from the source, for purposes of Part 70 fee assessment.
- (b) The annual emission statement covers the twelve (12) consecutive month time period starting January 1 and ending December 31. The annual emission statement must be submitted to:
- Indiana Department of Environmental Management  
Technical Support and Modeling Section, Office of Air Quality  
100 North Senate Avenue, P. O. Box 6015  
Indianapolis, Indiana 46206-6015
- (c) The annual emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

##### **C.20 Monitoring Data Availability [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)]**

- (a) With the exception of performance tests conducted in accordance with Section C- Performance Testing, all observations, sampling, maintenance procedures, and record keeping, required as a condition of this permit shall be performed at all times the equipment is operating at normal representative conditions.
- (b) As an alternative to the observations, sampling, maintenance procedures, and record keeping

of subsection (a) above, when the equipment listed in Section D of this permit is not operating, the Permittee shall either record the fact that the equipment is shut down or perform the observations, sampling, maintenance procedures, and record keeping that would otherwise be required by this permit.

- (c) If the equipment is operating but abnormal conditions prevail, additional observations and sampling should be taken with a record made of the nature of the abnormality.
- (d) If for reasons beyond its control, the operator fails to make required observations, sampling, maintenance procedures, or record keeping, reasons for this must be recorded.
- (e) At its discretion, IDEM may excuse such failure providing adequate justification is documented and such failures do not exceed five percent (5%) of the operating time in any quarter.
- (f) Temporary, unscheduled unavailability of staff qualified to perform the required observations, sampling, maintenance procedures, or record keeping shall be considered a valid reason for failure to perform the requirements stated in (a) above.

C.21 General Record Keeping Requirements [326 IAC 2-7-5(3)][326 IAC 2-7-6]

- (a) Records of all required monitoring data and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location for a minimum of three (3) years and available upon the request of an IDEM, OAQ, representative. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a written request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Records of required monitoring information shall include, where applicable:
  - (1) The date, place, and time of sampling or measurements;
  - (2) The dates analyses were performed;
  - (3) The company or entity performing the analyses;
  - (4) The analytic techniques or methods used;
  - (5) The results of such analyses; and
  - (6) The operating conditions existing at the time of sampling or measurement.
- (c) Support information shall include, where applicable:
  - (1) Copies of all reports required by this permit;
  - (2) All original strip chart recordings for continuous monitoring instrumentation;
  - (3) All calibration and maintenance records;
  - (4) Records of preventive maintenance shall be sufficient to demonstrate that failure to implement the Preventive Plan did not cause or contribute to a violation of any

limitation on emissions or potential to emit. To be relied upon subsequent to any such violation, these records may include, but are not limited to: work orders, parts inventories, and operator's standard operating procedures. Records of response steps taken shall indicate whether the response steps were performed in accordance with the Compliance Response Plan required by Section C - Compliance Monitoring Plan - Failure to take Response Steps, of this permit, and whether a deviation from a permit condition was reported. All records shall briefly describe what maintenance and response steps were taken and indicate who performed the tasks.

- (d) All record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

**C.22 General Reporting Requirements [326 IAC 2-7-5(3)(C)]**

---

- (a) To affirm that the source has met all the compliance monitoring requirements stated in this permit the source shall submit a Semi-annual Compliance Monitoring Report. Any deviation from the requirements and the date(s) of each deviation must be reported.
- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:
- Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue, P. O. Box 6015  
Indianapolis, Indiana 46206-6015
- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (d) Unless otherwise specified in this permit, any semi-annual report shall be submitted within thirty (30) days of the end of the reporting period.
- (e) All instances of deviations as described in Section B- Deviations from Permit Requirements and Conditions must be clearly identified in such reports.
- (f) Any corrective actions or response steps taken as a result of each deviation must be clearly identified in such reports.
- (g) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period.

The documents submitted pursuant to this condition do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

**Stratospheric Ozone Protection**

**C.23 Compliance with 40 CFR 82 and 326 IAC 22-1**

---

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and

emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.
- (b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

## SECTION D.1

## FACILITY OPERATION CONDITIONS

### Facility Description [326 IAC 2-7-5(15)]

- (a) Two (2) short stack # 1 and # 2 cupolas, known as EU#1 and EU#2, installed before 1960, each equipped with a baghouse, known as CE#1 and CE#2, exhausted to Stack #1 and Stack #2, respectively, capacity: 7.2 tons of molten material per hour, each.
- (b) Two (2) blowchambers, known as EU#3 and EU#4, installed before 1978, each equipped with a screenhouse, known as CE#3 and CE#4, (#1 and #2 screenhouse), capacity: 6.0 tons of fibers per hour, each.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions)

### Emission Limitations and Standards [326 IAC 2-7-5(1)]

#### D.1.1 Particulate Matter (PM) [326 IAC 6-3-2(c)]

Pursuant to 326 IAC 6-3 (Process operations), the allowable PM emission rate from:

- (a) Each of the two (2) cupolas (EU#1 and EU#2) shall not exceed 15.4 pounds per hour each when operating at a process weight rate of 7.2 tons of molten mineral per hour.
- (b) Each of the two (2) blowchambers (EU#3 and EU#4) shall not exceed 13.6 pounds per hour each when operating at a process weight rate of 6.0 tons of molten mineral per hour.
- (c) The pounds per hour emission limitations were calculated with the following formula:

Interpolation and extrapolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour}$$

#### D.1.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and their control devices.

### Compliance Determination Requirements

#### D.1.3 Testing Requirements [326 IAC 2-7-6(1),(6)]

- (a) During the period between 30 and 36 months after issuance of this permit, the Permittee shall perform PM testing of the exhaust stacks serving the two (2) cupolas (Stacks #1 and #2) utilizing Methods 5 or 17 (40 CFR 60, Appendix A) or other methods as approved by the Commissioner. This test shall be repeated at least once every five (5) years from the date of this valid compliance demonstration. In addition to these requirements, IDEM may require compliance testing when necessary to determine if the facility is in compliance.
- (b) The Permittee is not required to test the two (2) blowchambers by this permit. However, IDEM may require compliance testing when necessary to determine if these facilities are in compliance. If testing is required by IDEM, compliance with the PM limit specified in Condition D.1.1 shall be determined by a performance test conducted in accordance with

Section C - Performance Testing.

D.1.4 Particulate Matter (PM)

The baghouses (CE#1 and/or CE#2) and the screenhouses (CE#3 and/or CE#4) for PM control shall be in operation at all times when the cupolas (EU#1 and/or EU#2) and the blowchambers (EU#3 and/or EU#4) are in operation and exhausting to the outside atmosphere.

**Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]**

D.1.5 Visible Emissions Notations

- (a) Visible emission notations of the two (2) cupola (EU#1 and #2) and two blowchamber (EU#3 and #4) stack exhausts (Stack #1, #2, #3 and #4) shall be performed once per shift during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed.

D.1.6 Parametric Monitoring

The Permittee shall record the total static pressure drop across the baghouses (CE#1 and CE#2) and screenhouses (CE#3 and CE#4) used in conjunction with the two (2) cupolas and two (2) blowchambers, at least once daily when the insulation manufacturing processes are in operation when venting to the atmosphere. Unless operated under conditions for which the Compliance Response Plan specifies otherwise, the pressure drop across baghouses CE#1 and CE#2 shall be maintained within the range of 3.0 and 12.0 inches of water and the pressure drop across screenhouses CE#3 and CE#4 shall be maintained within the range of 0.2 and 10.0 inches of water or a range established during the latest stack test. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when the pressure reading is outside of the above mentioned range for any one reading.

The instrument used for determining the pressure shall comply with Section C - Pressure Gauge Specifications, of this permit, shall be subject to approval by IDEM, OAQ, and shall be calibrated at least once every six (6) months.

D.1.7 Baghouse and Screenhouse Inspections

- (a) An inspection shall be performed each calendar quarter of all bags controlling the two (2) cupolas when venting to the atmosphere. All defective bags shall be replaced or the associated tubesheet opening capped as long as no more than ten percent (10%) of the number of total bags; thirty (30) bags for the cupola #1 baghouse; and sixty (60) bags for the cupola #2 baghouse, are capped.



- (b) An inspection shall be performed each calendar quarter of all screens controlling the two (2) blowchambers when venting to the atmosphere. All defective screens shall be replaced.

#### **D.1.8 Broken or Failed Bag Detection**

---

In the event that bag failure has been observed.

- (a) The process associated with the affected compartments will be shut down or process charge suspended (process banked) immediately until the failed units have been repaired or replaced. Within eight (8) hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) hours of discovery of the failure and shall include a timetable for completion. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).
- (b) For single compartment baghouses, the process associated with the failed baghouse will be shut down or process charge suspended (process banked) immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

### **Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

#### **D.1.9 Record Keeping Requirements**

- 
- (a) To document compliance with Condition D.1.5, the Permittee shall maintain records of visible emission notations of the two (2) cupola and two (2) blowchamber stack exhausts once per shift.
  - (b) To document compliance with Condition D.1.6, the Permittee shall maintain the following:
    - (1) Daily records of the following operational parameters during normal operation when venting to the atmosphere:
      - (A) Inlet and outlet differential static pressure drop across the baghouse tube-sheet; and
      - (B) Cleaning cycle: frequency (baghouses that have cleaning cycles preset by the manufacturer, the Permittee can document the cycle once, versus re-documenting a preset every day) and differential pressure.
    - (2) Documentation of all response steps implemented, per event.
    - (3) Operation and preventive maintenance logs, including work purchases orders, shall be maintained.
    - (4) Quality Assurance/Quality Control (QA/QC) procedures.
    - (5) Operator standard operating procedures (SOP).
    - (6) Manufacturer's specifications or its equivalent.

- (7) Equipment "troubleshooting" contingency plan.
- (c) To document compliance with Condition D.1.7, the Permittee shall maintain records of the results of the inspections required under Condition D.1.7.
- (d) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

United States Mineral Products Company First Reopening No.: 069-13323  
d.b.a. Isolatek International Reopening by: Janet Mobley  
Huntington, Indiana  
Permit Reviewer:MES

Page 41 of 51  
OP No. T 069-5660-00021

## **SECTION D.2**

## **FACILITY OPERATION CONDITIONS**

**Facility Description [326 IAC 2-7-5(15)]**

- (c) Three (3) hoppers, known as EU#14, EU#15 and EU#17 (hopper #1, #2 and #4), installed in 1980, equipped with a baghouse, known as CE#9, exhausted to Stack #9, capacity: 5.0 tons of dry powdered binders per hour, each.
- (d) Two (2) hoppers, known as EU#16 and EU#18 (hopper #3 and #5), installed in 1980, equipped with a baghouse, known as CE#9, exhausted to Stack #9, capacity: 0.2 ton of dry powdered binders per hour, each.
- (e) One (1) live bottom hopper, known as EU#19, installed in 1980, equipped with a baghouse, known as CE#9, exhausted to Stack #9, capacity: 8.0 tons of mineral wool per hour.
- (f) One (1) granulator, known as EU#20, installed in 1980, equipped with a baghouse, known as CE#9, exhausted to Stack #9, capacity: 8.0 tons of mineral wool per hour.
- (g) One (1) bagger, known as EU#21, installed in 1980, equipped with a baghouse, known as CE#9, exhausted to Stack #9, capacity: 12.0 tons of blended product per hour.
- (h) Two (2) augers, known as EU#23 and EU#24, installed in 1980, equipped with a baghouse, known as CE#9, exhausted to Stack #9, capacity: 12.0 tons of blended product per hour, each.
- (i) One (1) portable hopper, known as EU#27 (portable hopper #3), installed in 1980, equipped with a baghouse, known as CE#9, exhausted to Stack #9, capacity: 0.2 ton of dry powdered binders per hour.
- (j) One (1) hammermill/cyclone, known as EU#28, installed in 1980, equipped with a baghouse, known as CE#9, exhausted to Stack #9, capacity: 2.0 tons of mineral wool per hour.
- (k) Two (2) portable hoppers, known as EU#25 and EU#26, (portable hoppers #1 and #2, respectively), installed in 1980, exhausted inside the building, capacity: 0.75 tons of dry powdered binders per hour, each.
- (l) Two (2) mineral wool balers, known as EU#5 and EU#6, installed before 1980, exhausted inside the building, capacity: 6.0 tons of baled mineral wool per hour, each.
- (m) One (1) front end mineral wool bagger, known as EU#7, installed in 1987, equipped with a baghouse, known as CE#5, exhausted to Stack #5, capacity: 5.0 tons of bagged mineral wool per hour.
- (n) One (1) mineral wool bin, known as EU#8, installed in 1983 or 1984, equipped with a equipped with a pneumatic conveyor that incorporates a totally enclosed air recycled system, capacity: 10.0 tons of mineral wool per hour.
- (o) One (1) gypsum silo, known as EU#9, installed before 1980, equipped with a baghouse, known as CE#8, exhausted to Stack #8, capacity: 54.0 tons of gypsum per hour.
- (p) One (1) chipped gypsum silo, known as EU#10, installed in 1991, equipped with a baghouse, known as CE#8, exhausted to Stack #8, capacity: 54.0 tons of gypsum per hour.
- (q) One (1) cement silo, known as EU#11, installed in 1990, equipped with a baghouse, known as CE#7, exhausted to Stack #7, capacity: 54.0 tons of Portland cement per hour.
- (r) One (1) batch blender, known as EU#12, installed in 1993, equipped with a baghouse, known as CE#6, exhausted to Stack #6, capacity: 5.0 tons of blended product per hour.
- (s) One (1) debaler, known as EU#13, installed in 1980, exhausted inside the building, capacity: 5.0 tons of mineral wool per hour.
- (t) One (1) raw material receiving yard, known as EU#29, installed prior to 1980, capacity: 216 tons of rock, slag and coke per hour.
- (u) One (1) batching station, known as EU#30, installed prior to 1980, capacity: 14.4 tons of rock and coke per hour.
- (v) One (1) ribbon blender, known as EU# 31, installed in 1988, equipped with a baghouse, known as CE#6, exhausted to Stack #6, capacity: 2.0 tons of dry powdered binders per year.
- (w) One (1) dedust oil tank, known as EU#34, installed prior to 1980, exhausted to Stack # 17, capacity: 7,000 gallons.
- (x) One (1) PEG400 VOC tank, known as EU#35, installed in 1990, capacity: 8,000 gallons.
- (y) One (1) Dedust oil tank, known as EU#38, installed in 1997, exhausted to Stack #21, capacity: 8,000 gallons.
- (z) Removed by AAT 069-12578
- (aa) One (1) mixed binder surge hopper scale system, known as EU#40, installed in 2000, equipped with an existing baghouse, known as CE#9, exhausted to

United States Mineral Products Company First Reopening No.: 069-13323  
d.b.a. Isolatek International Reopening by: Janet Mobley  
Huntington, Indiana  
Permit Reviewer:MES

Page 43 of 51  
OP No. T 069-5660-00021

# **Emission Limitations and Standards [326 IAC 2-7-5(1)]**

## **D.2.1 Particulate Matter (PM) [326 IAC 6-3]**

Pursuant to 326 IAC 6-3 (Process Operations), the allowable PM emission rates from the indicated facilities shall not exceed the PM emission limitations specified at the specified process weight rates listed in following table:

<b>Emission Unit(s)</b>	<b>Process Weight Rate (tons per hour)</b>	<b>Allowable PM Emission Rate (pounds per hour)</b>
EU#5 and EU#6	6.0, each	13.6, each
EU#7	5.0	12.1
EU#8	10.0	19.2
EU#9 and EU#10	54.0, each	45.3, each
EU#11	54.0	45.3
EU#12 and EU#13	5.0, each	12.1, each
EU#14 and EU#15	5.0, each	12.1, each
EU#16	0.2	1.40
EU#17 and EU#40	5.0, each	12.1 total
EU#18	0.2	1.40
EU#19 and EU#20	8.0, each	16.5, each
EU#21, EU#23 & EU#24	12.0, each	21.7, each
EU#25 and EU#26	0.75, each	3.38, each
EU#27	0.2	1.40
EU#28	2.0	6.52
EU#31	2.0	6.52

The pounds per hour limitations were calculated with the following equations:

Interpolation and extrapolation of the data for the process weight rate up to 60,000 pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

where

E = rate of emission in pounds per hour; and  
P = process weight rate in tons per hour

and

Interpolation and extrapolation of the data for the process weight rate in excess of 60,000 pounds per hour shall be accomplished by use of the equation:

$$E = 55.0 P^{0.11} - 40 \quad \text{where} \quad \begin{array}{l} E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour} \end{array}$$

**D.2.2 Prevention of Significant Deterioration [326 IAC 2-2]**

Any change or modification for these emission units which may increase potential to emit to 25 tons per year for PM and 15 tons per year for PM<sub>10</sub> shall require approval from IDEM, OAQ prior to making the change.

**D.2.3 Part 70 Permits: source modifications [326 IAC 2-7-10.5]**

The particulate matter (PM) and PM<sub>10</sub> emissions from EU#40 shall not exceed 1.14 pounds per hour in order to avoid the requirements of 326 IAC 2-7-10.5.

**D.2.4 Preventive Maintenance Plan [326 IAC 2-7-5(13)]**

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for facilities, EU#7 - EU#12, EU#14, EU#15, EU#17, EU#19 - EU#24 and EU#27, and their control devices.

**Compliance Determination Requirements**

**D.2.5 Testing Requirements [326 IAC 2-7-6(1),(6)]**

The Permittee is not required to test these facilities by this permit. However, IDEM may require compliance testing at any specific time when necessary to determine if these facilities are in compliance. If testing is required by IDEM, compliance with the particulate matter limits specified in Condition D.2.1 shall be determined by a performance test conducted in accordance with Section C - Performance Testing.

**D.2.6 Particulate Matter (PM)**

The baghouses (CE#5 - CE#9) for PM control shall be in operation at all times when their facilities are in operation and exhausting to the outside atmosphere.

**Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]**

**D.2.7 Visible Emissions Notations**

- (a) Visible emission notations of emission units EU#7 - EU#12, EU#14, EU#15, EU#17, EU#19, EU#24 and EU#27 stack exhausts (Stack #5, #6, #7, #8 and #9) shall be performed once per shift during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed.

**D.2.8 Parametric Monitoring**

The Permittee shall record the total static pressure drop across the baghouses (CE#5 - CE#9) used in conjunction with emission units EU# 7, 8, 10, 11, 12, 14, 15, 16, 17, 18, 19, 20, 21, 22, 27 and 28

at least once daily when the insulation manufacturing processes are in operation when venting to the atmosphere. Unless operated under conditions for which the Compliance Response Plan specifies otherwise, the pressure drop across baghouses CE#5 and CE#6 shall be maintained within the range of 1.0 and 6.0 inches of water, the pressure drop across baghouses CE#7 and CE#8 shall be maintained within the range of 1.0 and 6.0 inches of water, and the pressure drop across baghouse CE#9 shall be maintained within the range of 0.2 and 6.0 inches of water or a range established during the latest stack test. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when the pressure reading is outside of the above mentioned range for any one reading.

The instrument used for determining the pressure shall comply with Section C - Pressure Gauge Specifications, of this permit, shall be subject to approval by IDEM, OAQ, and shall be calibrated at least once every six (6) months.

#### **D.2.9 Baghouse Inspections**

An inspection shall be performed each calendar quarter of all bags controlling the insulation manufacturing operations when venting to the atmosphere. All defective bags shall be replaced or the associated tubesheet opening capped as long as no more than ten percent (10%) of the number of total bags are capped.

#### **D.2.10 Broken or Failed Bag Detection**

In the event that bag failure has been observed.

- (a) The process associated with the affected compartments will be shut down immediately until the failed units have been repaired or replaced. Within eight (8) hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) hours of discovery of the failure and shall include a timetable for completion. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).
- (b) For single compartment baghouses, the process associated with the failed baghouse will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

### **Record Keeping and Reporting Requirement [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

#### **D.2.11 Record Keeping Requirements**

- (a) To document compliance with Condition D.2.6, the Permittee shall maintain records of visible emission notations of the facilities stack exhausts once per shift.
- (b) To document compliance with Condition D.2.7, the Permittee shall maintain the following:
  - (1) Daily records of the following operational parameters during normal operation when venting to the atmosphere:
    - (A) Inlet and outlet differential static pressure; and
    - (B) Cleaning cycle: frequency and differential pressure.



- (2) Documentation of all response steps implemented, per event.
  - (3) Operation and preventive maintenance logs, including work purchases orders, shall be maintained.
  - (4) Quality Assurance/Quality Control (QA/QC) procedures.
  - (5) Operator standard operating procedures (SOP).
  - (6) Manufacturer's specifications or its equivalent.
  - (7) Equipment "troubleshooting" contingency plan.
  - (8) Documentation of the dates vents are redirected.
- (b) To document compliance with Condition D.2.8, the Permittee shall maintain records of the results of the inspections required under Condition D.2.8 and the dates the vents are re-directed.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY**

**PART 70 OPERATING PERMIT  
CERTIFICATION**

Source Name: United States Mineral Products Company d.b.a. Isolatek International  
Source Address: 701 North Broadway, Huntington, Indiana 46750  
Mailing Address: P.O. Box 5006, Huntington, Indiana 46750  
Part 70 Permit No.: T 069-5660-00021

**This certification shall be included when submitting monitoring, testing reports/results  
or other documents as required by this permit.**

Please check what document is being certified:

- 9 Annual Compliance Certification Letter
- 9 Test Result (specify) \_\_\_\_\_
- 9 Report (specify) \_\_\_\_\_
- 9 Notification (specify) \_\_\_\_\_
- 9 Other (specify) \_\_\_\_\_

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT**  
**OFFICE OF AIR QUALITY**  
**COMPLIANCE BRANCH**  
**P.O. Box 6015**  
**100 North Senate Avenue**  
**Indianapolis, Indiana 46206-6015**  
**Phone: 317-233-5674**  
**Fax: 317-233-5967**

**PART 70 OPERATING PERMIT**  
**EMERGENCY/DEVIATION OCCURRENCE REPORT**

Source Name: United States Mineral Products Company d.b.a. Isolatek International  
Source Address: 701 North Broadway, Huntington, Indiana 46750  
Mailing Address: P.O. Box 5006, Huntington, Indiana 46750  
Part 70 Permit No.: T 069-5660-00021

This form consists of 2 pages

Page 1 of 2

Check either No. 1 or No.2

- 9** 1. This is an emergency as defined in 326 IAC 2-7-1(12)
- ☐ The Permittee must notify the Office of Air Quality (OAQ), within four **(4)** business hours (1-800-451-6027 or 317-233-5674, ask for Compliance Section); and
  - ☐ The Permittee must submit notice in writing or by facsimile within two **(2)** days (Facsimile Number: 317-233-5967), and follow the other requirements of 326 IAC 2-7-16

- 9** 2. This is a deviation, reportable per 326 IAC 2-7-5(3)(C)
- ☐ The Permittee must submit notice in writing within ten **(10)** calendar days

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:

Control Equipment:

Permit Condition or Operation Limitation in Permit:

Description of the Emergency/Deviation:

Describe the cause of the Emergency/Deviation:

If any of the following are not applicable, mark N/A

Page 2 of 2

Date/Time Emergency/Deviation started:
Date/Time Emergency/Deviation was corrected:
Was the facility being properly operated at the time of the emergency/deviation?    Y    N Describe:
Type of Pollutants Emitted: TSP, PM-10, SO <sub>2</sub> , VOC, NO <sub>x</sub> , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency/deviation:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by: \_\_\_\_\_

Title / Position: \_\_\_\_\_

Date: \_\_\_\_\_

Phone: \_\_\_\_\_

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE DATA SECTION**

**PART 70 OPERATING PERMIT  
SEMI-ANNUAL COMPLIANCE MONITORING REPORT**

Source Name: United States Mineral Products Company d.b.a. Isolatek International  
Source Address: 701 North Broadway, Huntington, Indiana 46750  
Mailing Address: P.O. Box 5006, Huntington, Indiana 46750  
Part 70 Permit No.: T 069-5660-00021

Months: \_\_\_\_\_ to \_\_\_\_\_ Year: \_\_\_\_\_

This report is an affirmation that the source has met all the compliance monitoring requirements stated in this permit. This report shall be submitted semi-annually. Any deviation from the compliance monitoring requirements and the date(s) of each deviation must be reported. Additional pages may be attached if necessary. This form can be supplemented by attaching the Emergency/Deviation Occurrence Report. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period".

**9 NO DEVIATIONS OCCURRED THIS REPORTING PERIOD**

**9 THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD.**

<b>Compliance Monitoring Requirement</b> (e.g. Permit Condition D.1.3)	<b>Number of Deviations</b>	<b>Date of Each Deviation</b>

Form Completed By: \_\_\_\_\_

Title/Position: \_\_\_\_\_

Date: \_\_\_\_\_

Phone: \_\_\_\_\_

Attach a signed certification to complete this report.